



Application Industry: Polycarboxylate Superplasticizer Power Plant Desulfurization
Landfill Leachate Water Treatment

Product Name: Antifoam RK-600P

RK-600P is a non-silicone defoamer grafted with functional modified polyether. It has good dispersibility, fast defoaming and strong dynamic foam suppression ability performances. It is mainly used for defoaming of polycarboxylate superplasticizer, power plant desulfurization, landfill leachate and water treatment, etc.

Product Characteristics

Defoaming quickly, good dynamic antifoaming performance

Good dispersion

Excellent properties in the widely pH values

No negative impacts on subsequent processes

Main physical and chemical properties:

Item	Index
Appearance	Colorless to pale yellow transparent liquid
Viscosity (25°C)	100-1000mpa·s
pH	5.0~7.0
Ionicity	Nonionic

Application Process:

Added directly during the production, it is recommended to continuously added by metering pumps. The volume of addition is 0.5%~0.6%. Based on your specific conditions, optimum volume of addition could be adjusted. But our kindly advice is that do not dilute, as the performance will be affected.

Key application

Polycarboxylate superplasticizer

Power plant desulfurization

Landfill leachate

Water treatment

Industrial process that cannot use silicone defoamer

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses



Information of manufacturers and products

Product name	Antifoam
Model	RK-600P
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: No 1267Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Polyether

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

Packaging & Storage

Package	25kg/ 50kg/200kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) , avoid direct sun light, shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application.